

D and HD Series

2-Wire Round/Rectangular Zone Dampers

D-XX
HD-XXXX

The D Series dampers are galvanized steel, single-blade dampers with a 24 volt spring return actuator. These dampers are shipped complete and ready for installation. They are rated for duct systems with less than 1.0" WC. The D Series damper has a simple adjustment for setting the minimum position.



Features and Benefits:

- Compatible with most zone control panels
- 24-gauge steel shell
- Tight seal gasket
- 24V synchronous motor
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty: 5 years

Specifications:

| | |
|-----------------------------|--|
| Construction | 24-gauge steel shell |
| Sizes | 4", 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20" |
| Damper Actuator Type | 24VAC, 10VA, 2-wire power close/spring open |

The HD Series dampers are extruded aluminum parallel blade dampers with a 24 volt spring return actuator. The HD Series dampers can be installed in any position. They are rated for duct systems with less than 1.0" WC. The damper has a simple adjustment for setting the minimum position.



Features and Benefits:

- Compatible with most zone control panels
- Extruded aluminum
- 24V synchronous motor
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty: 5 years

Specifications:

| | |
|-----------------------------|---|
| Construction | Extruded aluminum |
| Sizes | 6" x 6" to 36" x 24" side-mount or bottom-mount |
| Damper Actuator Type | 24VAC, 10VA, 2-wire power close/spring open |

5351 East Thompson Road Suite 142
Indianapolis, IN 46237
P: 888.359.0362
F: 317.489.5204
info@iOhvaccontrols.com
www.iOhvaccontrols.com